

## Webviewer Tip

If you show a website in a webviewer (Filemaker) or a htmlviewer (Real Studio), you can have a little problem. Some links in the web viewer may have target = \_blank. This links now open in Safari (Mac) or Internet Explorer (Win) if the user clicks on a link. But you may not want that and prefer to keep the user inside your web viewer.

A solution is to change the target of the links by using our plugin and a little bit of javascript.

In **Filemaker** you can do this:

```
MBS("WebView.RunJavaScript"; "browser"; "for (i = 0; i <
document.links.length; i++)
{ if (document.links[i].target == '_blank')
document.links[i].target = ''; }")
```

"browser" is the name of the web viewer control on your layout. Simply run it in a calculation like a script step for setting a variable.

In **Real Studio** you go like this:

```
dim javascript as string = "for (i = 0; i <
document.links.length; i++)
{ if (document.links[i].target == '_blank')
document.links[i].target = ''; }"

if TargetWin32 then
    call HTMLViewer1.IERunJavaScriptMBS javascript
elseif TargetMachO then
    call HTMLViewer1.EvaluateJavaScriptMBS javascript
else
    break // platform not supported
end if
```

As you see we call IERunJavaScriptMBS on Windows and EvaluateJavaScriptMBS on Mac.